

# PVC-insulated cord (flat) X03VH-H

**conductor material:** bare copper  
**conductor construction:** fine stranded class 6  
**insulation:** PVC  
**bending radius, fixed installation:** 6 x DA  
**flame retardant:** acc. to IEC 60332-1-2  
**sheathing material:** PVC

**core identification:** colours acc. VDE 0293 (HD308)  
**nominal voltage U<sub>0</sub>:** 300 V  
**nominal voltage U:** 300 V

**Application:** Connecting cable for lightning electrical appliances, radio appliances, table lamps, watches etc. for light duty mechanical appliances in households, kitchen and office rooms, as far as this is permitted in the relevant appliances regulations.

**Austria:** YZWL



The products and information presented here are for technical calculation only. They are subject to technical progress and in no way represent the ability of shipment. Outer diameters are approximately.

table: technical data X03VH-H

Art.-Nr.	part name	RI [Ω/km]	I <sub>bl</sub> [A]	B [mm]	H [mm]	CU	G [kg/km]
033520	X03VH-H 02X0,75 BR	26	15	3,1	6,3	14,4	26
033521	X03VH-H 02X0,75 SW	26	15	3,1	6,3	14,4	26
033522	X03VH-H 02X0,75 WS	26	15	3,1	6,3	14,4	26