

TPE -insulated, numbered, PUR sheath

Product Description

Well-proven, reliable;Wide range use;All-weather control cable



Application range

- In power chains or moving machine parts
- Especially in wet areas of machine tools and transfer lines subject to average mechanical stress
- Mechanical engineering
- Construction machinery
- Assembly lines, production lines, in all kinds of machines

Benefits

- Well-proven, reliable
- Wide range use
- All-weather control cable

Design

- Extra fine strands of plain copper wires (Class 6)
- Core insulation: TPE
- Cores twisted together in extremely short lay lengths
- Nonwoven wrapping
- Polyurethane sheath (PUR), grey (RAL 7001)

Approvals (Norm references)

- For travel distances up to 100 m (horizontal)
- Usage in Power Chains: Please comply with the assembly guidelines Appendix T3

Product features

- Low adhesive surface



- Oil resistant
- Halogen-free and flame retardant (IEC 60332-1-2)
- In dry, damp or wet interiors under medium mechanical load conditions
- Designed for up to 5 million bending change cycles in the power chain

Technical Data

Core identification code

Black with white numbers acc. to VDE 0293

Based on

VDE 0250/0281/0282

Specific insulation resistance

> 20 GOhm x cm

Conductor stranding

Extra fine wire according to VDE 0295 Class 6 /
IEC 60228 Class 6

Minimum bending radius

For flexible applications: 5 x outer diameter
Fixed installation: 3 x outer diameter

Rated voltage

300/500 V

Test voltage

3000 V

Protective conductor

G = with protective conductor GN/YE

X = without protective conductor

Range of temperature

Flexing: -40°C up to +80°C

Fixed installation: -50°C up to +80 °C During installation:
-40°C up to +80 °C

Article List

Part number	Number of cores and mm ² per conductor	Outer diameter in mm	Copper index kg/km	Weight kg/km
0027530	2 X 0,5	5.1	10.0	34
0027531	3 G 0,5	5.5	14.0	40
0027532	5 G 0,5	6.6	24.0	55
0027533	6 G 0,5	7.1	29.0	63
0027534	7 G 0,5	7.7	34.0	76
0027535	12 G 0,5	9.1	58.0	114
0027536	18 G 0,5	10.9	86.0	165
0027537	20 G 0,5	11.5	96.0	180
0027538	25 G 0,5	13.4	120.0	219
0027540	30 G 0,5	13.6	144.0	251
0027541	36 G 0,5	14.7	173.0	290
0027545	2 X 0,75	5.6	14.0	42
0027546	3 G 0,75	6.0	22.0	50

0027547	4 G 0,75	6.7	29.0	60
0027548	5 G 0,75	7.3	36.0	71
0027549	7 G 0,75	8.8	50.0	99
0027550	12 G 0,75	10.3	86.0	158
0027551	18 G 0,75	12.4	130.0	219
0027552	20 G 0,75	13.3	144.0	240
0027553	25 G 0,75	15.5	180.0	309
0027555	36 G 0,75	16.9	259.0	411
0027560	2 X 1,0	6.0	19.0	50
0027561	3 G 1,0	6.5	29.0	61
0027562	4 G 1,0	7.2	38.0	70
0027563	5 G 1,0	7.8	48.0	93
0027564	7 G 1,0	9.5	67.0	122
0027565	12 G 1,0	11.2	115.0	196
0027566	18 G 1,0	13.7	173.0	274
0027567	20 G 1,0	14.4	192.0	300
0027568	25 G 1,0	16.8	240.0	385
0027570	30 G 1,0	17.0	288.0	444
0027571	36 G 1,0	18.6	346.0	516
0027575	2 X 1,5	6.7	29.0	68
0027576	3 G 1,5	7.3	43.0	83
0027586	4 G 1,5	8.0	58.0	100
0027577	5 G 1,5	9.0	72.0	128
0027578	7 G 1,5	10.7	101.0	177
0027579	12 G 1,5	12.7	173.0	275
0027580	18 G 1,5	15.2	259.0	405
0027582	25 G 1,5	18.8	360.0	565
0027584	30 G 1,5	18.8	432.0	652
0027585	36 G 1,5	20.6	518.0	759
0027587	41 G 1,5	22.4	614.0	978
0027370	3 G 2,5	8.9	72.0	121
0027371	4 G 2,5	9.9	96.0	163
0027372	5 G 2,5	11.0	120.0	196
0027373	7 G 2,5	13.4	168.0	266
0027374	12 G 2,5	15.8	288.0	446
0027375	18 G 2,5	18.9	432.0	665
0027376	25 G 2,5	23.5	600.0	929

Footnote:

All product related values as shown are nominal values unless specified differently. Further values, e.g. tolerances we submit on request - if available and released for publication.

Copper price basis: EUR 150 / 100 kg; For utilization and definition of 'Metal price basis' and 'Metal index' see Appendix



T17

Please find our standard lengths at: www.lappkabel.de/en/cable-standardlengths

Packaging size: Coil \leq 30 kg and \leq 250 m, otherwise drum

Please specify the desired packaging size (e.g. 1 x 500 m drum or 5 x 100 m coils)

Photographs are not to scale and do not represent detailed images of the respective products.