

H05VV5-F (NYSLYÖ-JZ) flexible, number coded, oil resistant, meter marking



A



Technical data

- Control cable, special PVC with oil resistant outer jacket to DIN VDE 0281 part 13, HD 21.13S1 and IEC 60227/75
- Temperature range**
flexing -5°C to +70°C
fixed installation -40°C to +70°C
- Nominal voltage** U_0/U 300/500 V
- Test voltage** 2000 V, 5 min.
- Breakdown voltage** min. 4000 V
- Insulation resistance**
min. 20 MΩm x km
- Minimum bending radius**
flexing 7,5x cable Ø
fixed installation 4x cable Ø
- Radiation resistance**
up to 80x10⁶ cJ/kg (up to 80 Mrad)

Cable structure

- Bare copper, fine wire stranded conductor to DIN VDE 0295 cl. 5, BS 6360 cl. 5, HD 383 and IEC 60228 cl. 5
- Special PVC core insulation T12 to DIN VDE 0281 part 1
- Black cores with white figure imprint to DIN VDE 0293
- Green-yellow earth core in the outer layer (3 cores and above)
- Cores stranded in layers with optimal lay-length
- Special PVC outer jacket, TM5 to DIN VDE 0281 part 1, HD 21.1.S4/A16
- Colour grey (RAL 7001)
- with meter marking, change-over in 2009

Properties

- PVC self-extinguishing and flame retardant according to VDE 0482-332-1-2, DIN EN 60332-1-2/ IEC 60332-1 (equivalent DIN VDE 0472 part 804 test method B)
- Oil resistant to HD/EN 60811-2-1
- The materials used in manufacture are cadmium-free and contain no silicone and free from substances harmful to the wetting properties of lacquers

Note

- G = with green-yellow earth core; x = without green-yellow earth core (OZ).
- AWG sizes are approximate equivalent values. The actual cross-section is in mm².
- screened analogue type:**
H05VVC4V5-K (NYSLYCYÖ-JZ), see page A 29

Application

These cables are used for flexible use for medium mechanical stresses with free movement without tensile stress or forced movements in dry, moist and wet rooms but not suitable for open air. These are designed as control and connecting cables to machines, tool machineries, conveyor belts and production lines.

These cables are not effected to the chemical influences. Cables for moist and wet rooms, specially used for machines in breweries, bottling plants and car washing stations.

These cables may be allowed to move once installed provided that the cables are not mechanically stressed during movement.

CE= The product is conformed with the EC Low-Voltage Directive 2006/95/EG.

Part No.	No. cores x cross-sec. mm ²	Outer ø app. mm	Cop. weight kg / km	Weight app. kg / km	AWG-No.	Part No.	No. cores x cross-sec. mm ²	Outer ø app. mm	Cop. weight kg / km	Weight app. kg / km	AWG-No.
13122	2 x 0,5	5,9	9,7	46,0	20	13123	2 x 0,75	6,3	14,1	52,0	18
13001	3 G 0,5	6,2	14,4	54,0	20	13013	3 G 0,75	6,7	21,6	68,0	18
13002	4 G 0,5	6,7	19,0	65,0	20	13014	4 G 0,75	7,3	29,0	82,0	18
13003	5 G 0,5	7,4	24,0	80,0	20	13015	5 G 0,75	8,3	36,0	107,0	18
13004	6 G 0,5	8,4	29,0	104,0	20	13016	6 G 0,75	9,0	43,0	132,0	18
13005	7 G 0,5	9,1	33,6	119,0	20	13017	7 G 0,75	9,7	50,0	145,0	18
13920	8 G 0,5	9,6	38,0	134,0	20	13926	8 G 0,75	10,4	58,0	189,0	18
13006	9 G 0,5	10,6	43,0	136,0	20	13018	9 G 0,75	11,5	65,0	194,0	18
13921	10 G 0,5	10,8	48,0	166,0	20	13019	12 G 0,75	12,1	86,0	231,0	18
13007	12 G 0,5	11,2	58,0	186,0	20	13927	14 G 0,75	12,4	101,0	274,0	18
13922	14 G 0,5	11,7	67,0	215,0	20	13020	18 G 0,75	14,0	130,0	313,0	18
13008	18 G 0,5	13,0	86,0	251,0	20	13021	25 G 0,75	17,0	180,0	461,0	18
13009	25 G 0,5	16,0	120,0	349,0	20	13928	27 G 0,75	17,1	195,0	493,0	18
13923	27 G 0,5	16,1	129,6	373,0	20	13022	34 G 0,75	19,1	245,0	614,0	18
13010	34 G 0,5	17,7	163,0	480,0	20	13929	36 G 0,75	19,1	259,0	646,0	18
13924	36 G 0,5	17,7	172,0	510,0	20	13126	41 G 0,75	21,3	295,0	730,0	18
13125	41 G 0,5	19,8	196,0	570,0	20	13023	50 G 0,75	23,2	360,0	896,0	18
13011	50 G 0,5	21,5	240,0	658,0	20	13024	61 G 0,75	25,8	439,0	1030,0	18
13012	61 G 0,5	23,0	293,0	780,0	20	13930	65 G 0,75	27,1	468,0	1071,0	18
13925	65 G 0,5	25,3	312,0	810,0	20						

Dimensions and specifications may be changed without prior notice. (RA01)

Continuation ▶

H05VV5-F (NYSLYÖ-JZ) flexible, number coded,

oil resistant, meter marking



Part No.	No. cores x cross-sec. mm ²	Outer ø app. mm	Cop. weight kg / km	Weight app. kg / km	AWG-No.
13119	2 x 1	6,6	19,0	66,0	17
13025	3 G 1	7,0	29,0	78,0	17
13026	4 G 1	7,6	38,0	104,0	17
13027	5 G 1	8,7	48,0	123,0	17
13028	6 G 1	9,5	58,0	152,0	17
13029	7 G 1	10,2	67,0	183,0	17
13931	8 G 1	11,0	77,0	220,0	17
13030	9 G 1	12,1	86,0	230,0	17
13031	12 G 1	12,7	115,0	269,0	17
13932	14 G 1	13,3	134,0	361,0	17
13032	18 G 1	15,0	173,0	400,0	17
13933	19 G 1	15,0	183,0	413,0	17
13033	25 G 1	18,0	240,0	546,0	17
13934	27 G 1	18,0	259,0	582,0	17
13034	34 G 1	20,6	326,0	724,0	17
13124	36 G 1	21,0	348,0	775,0	17
13935	37 G 1	21,0	355,0	785,0	17
13127	41 G 1	22,5	392,0	822,0	17
13035	50 G 1	24,5	480,0	1052,0	17
13036	61 G 1	26,0	586,0	1265,0	17
13936	65 G 1	28,1	624,0	1315,0	17
13120	2 x 1,5	7,3	29,0	77,0	16
13037	3 G 1,5	7,9	43,0	97,0	16
13038	4 G 1,5	8,7	58,0	128,0	16
13039	5 G 1,5	9,6	72,0	149,0	16
13040	6 G 1,5	10,7	86,0	196,0	16
13041	7 G 1,5	11,8	101,0	216,0	16
13937	8 G 1,5	13,2	115,0	271,0	16
13042	9 G 1,5	13,5	130,0	282,0	16
13043	12 G 1,5	14,4	173,0	324,0	16
13121	14 G 1,5	15,3	202,0	372,0	16
13044	18 G 1,5	17,2	259,0	485,0	16
13938	19 G 1,5	17,2	274,0	495,0	16
13045	25 G 1,5	21,7	360,0	671,0	16
13939	27 G 1,5	21,7	389,0	695,0	16
13046	32 G 1,5	22,4	461,0	820,0	16
13047	34 G 1,5	24,1	490,0	881,0	16
13940	36 G 1,5	24,4	518,0	905,0	16
13941	37 G 1,5	24,4	532,0	920,0	16
13128	41 G 1,5	26,3	590,0	1085,0	16
13048	50 G 1,5	28,9	720,0	1381,0	16
13049	61 G 1,5	30,8	878,0	1640,0	16
13942	65 G 1,5	32,2	963,0	1730,0	16

Part No.	No. cores x cross-sec. mm ²	Outer ø app. mm	Cop. weight kg / km	Weight app. kg / km	AWG-No.
13943	2 x 2,5	9,1	48,0	110,0	14
13050	3 G 2,5	9,6	72,0	154,0	14
13051	4 G 2,5	10,8	96,0	212,0	14
13052	5 G 2,5	11,6	120,0	242,0	14
13053	7 G 2,5	14,2	168,0	350,0	14
13945	8 G 2,5	16,1	192,0	379,0	14
13054	12 G 2,5	17,7	288,0	543,0	14
13946	14 G 2,5	19,0	336,0	611,0	14
13055	18 G 2,5	21,4	432,0	787,0	14
13056	25 G 2,5	26,1	600,0	1175,0	14
13947	27 G 2,5	26,2	648,0	1280,0	14
13057	34 G 2,5	29,5	816,0	1529,0	14
13948	36 G 2,5	29,6	864,0	1791,0	14
13949	41 G 2,5	32,0	984,0	1905,0	14
13058	50 G 2,5	35,0	1200,0	2290,0	14
13059	61 G 2,5	37,1	1464,0	2724,0	14

Dimensions and specifications may be changed without prior notice. (RA01)

Our Service on the Internet

The screenshot shows the HELUKABEL website interface. At the top, there are navigation links: Download centre, Logistic centre, Company, Products, Quality, News, Contact, Service, Opinion, and Imprint. A search bar is located on the right. Below the navigation, there is a 'You are here' breadcrumb trail: Home > News > Fairs. A 'News' sidebar contains links for Fairs, Job posting, Special offer's, and Press Contact. The main content area features a 'Fairs' section with a dropdown menu listing News, Fairs, Job posting, Special offer's, and Press Contact. Below this, there are three images of trade fair booths. On the right, there is a 'HELUKABEL world-wide' section with a world map and a 'please select...' dropdown menu.

Trade fair appointments

In the Internet, you will find the trade fairs we are participating in, both in Germany and abroad. Please visit our Website and arrange an appointment with us. We are looking forward to your visit.

www.helukabel.de