

KOMPOFLEX® JZ-500-C halogen-free, microbes resistant, Cu-screende, EMC-preferred type, meter marking



A



Technical data

- Screened microbes resistant, halogen-free special control cable in adapted to DIN VDE 0281 part 13 and E DIN VDE 0245
- **Temperature range**
flexing -30°C to + 90°C
fixed installation -40°C to +100°C
- **Nominal voltage** U₀/U 300/500 V
- **Test voltage**
core/core 4000 V
core/screen 2000 V
- **Insulation resistance**
min. 20 MΩm x km
- **Minimum bending radius**
flexing 7,5x cable Ø
fixed installation 4x cable Ø
- **Coupling resistance**
max. 250 Ωm/km
- **Radiation resistance**
up to 100x10⁶ cJ/kg (up to 100 Mrad)

Cable structure

- Tinned copper, fine wire conductors, bunch stranded to DIN VDE 0295 cl. 5, BS 6360 cl. 5 and IEC 60228 cl. 5
- Special thermoplastic polymer core insulation
- Black cores with continuous white numbering according to DIN VDE 0293
- Green-yellow earth core in the outer layer (3 cores and above)
- Cores stranded in layers with optimal lay-length
- Inner-sheath to special thermoplastic polymer
- Screen of tinned cu braid, coverage approx. 85%
- Outer sheath, special thermoplastic polymer
- Colour black (RAL 9005)
- with meter marking, change-over in 2009

Properties

- **Resistant to**
UV-radiation, Oxygene, Ozone, Microbes, Hydrofluoric acid, Hydrochloric acid and diluted sulfuric acid
- Low adhesion
- The materials used in manufacture are cadmium-free and contain no silicone and free from substances harmful to the wetting properties of lacquers

Note

- G = with green-yellow earth core; x = without green-yellow earth core (OZ).
- AWG sizes are approximate equivalent values. The actual cross-section is in mm².
- **unscreened analogue type:**
KOMPOFLEX® JZ-500, see page A 87

Application

Die mehr als robuste Universalleitung.

This cable is specially installed in rubbish, sewage-treatment plants, composting works, animal stalls and greenhouses. The inner sheaths of those cables raise the mechanical stress. Suitable for installation for flexible use for medium mechanical, stresses with free movement without tensile stress or forced movements in dry, moist and wet rooms as well as outside. The high flexibility of this cable type makes it quick and easy to install.

This screened cable is ideal for use in data signal transmission free from interferences for measurement and control engineering technology.

EMC = Electromagnetic compatibility

To optimise the EMC features we recommend a large round contact of the copper braiding on both ends.

CE = The product is conformed with the EC Low-Voltage Directive 2006/95/EG.

Part No.	No. cores x cross-sec. mm ²	Outer ø app. mm	Cop. weight kg / km	Weight app. kg / km	AWG-No.	Part No.	No. cores x cross-sec. mm ²	Outer ø app. mm	Cop. weight kg / km	Weight app. kg / km	AWG-No.
26217	2 x 0,5	6,9	41,0	68,0	20	26245	2 x 1	7,9	54,0	98,0	17
26218	3 G 0,5	7,2	45,0	84,0	20	26246	3 G 1	8,2	64,0	102,0	17
26219	4 G 0,5	7,8	54,0	95,0	20	26247	4 G 1	8,9	76,0	145,0	17
26220	5 G 0,5	8,3	66,0	107,0	20	26248	5 G 1	9,5	89,0	171,0	17
26221	7 G 0,5	9,5	79,0	135,0	20	26249	7 G 1	11,0	114,0	210,0	17
26222	12 G 0,5	11,3	137,0	195,0	20	26250	12 G 1	13,1	186,0	350,0	17
26223	18 G 0,5	13,1	156,0	278,0	20	26251	18 G 1	15,4	284,0	488,0	17
26224	20 G 0,5	13,8	173,0	310,0	20	26252	20 G 1	16,0	325,0	545,0	17
26225	25 G 0,5	15,7	250,0	406,0	20	26253	25 G 1	18,3	387,0	690,0	17
26226	30 G 0,5	16,0	297,0	520,0	20	26254	30 G 1	18,8	457,0	770,0	17
26227	34 G 0,5	17,4	316,0	571,0	20	26255	34 G 1	20,3	500,0	811,0	17
26228	42 G 0,5	18,9	360,0	651,0	20	26256	42 G 1	21,8	590,0	996,0	17
26229	50 G 0,5	20,9	407,0	760,0	20	26257	50 G 1	24,0	681,0	1320,0	17
26230	61 G 0,5	22,9	520,0	911,0	20	26258	61 G 1	26,2	710,0	1480,0	17
26231	2 x 0,75	7,6	46,0	88,0	18	26259	2 x 1,5	8,4	64,0	130,0	16
26232	3 G 0,75	7,8	57,0	98,0	18	26260	3 G 1,5	9,0	82,0	154,0	16
26233	4 G 0,75	8,3	63,0	112,0	18	26261	4 G 1,5	9,6	99,0	165,0	16
26234	5 G 0,75	9,1	76,0	130,0	18	26262	5 G 1,5	10,5	123,0	197,0	16
26235	7 G 0,75	10,4	100,0	185,0	18	26263	7 G 1,5	12,1	148,0	305,0	16
26236	12 G 0,75	12,5	175,0	294,0	18	26264	12 G 1,5	14,9	274,0	435,0	16
26237	18 G 0,75	14,3	240,0	357,0	18	26265	18 G 1,5	17,1	386,0	642,0	16
26238	20 G 0,75	15,2	262,0	404,0	18	26266	20 G 1,5	18,0	401,0	718,0	16
26239	25 G 0,75	17,6	306,0	510,0	18	26267	25 G 1,5	20,7	531,0	803,0	16
26240	30 G 0,75	18,1	340,0	561,0	18	26268	30 G 1,5	21,1	598,0	961,0	16
26241	34 G 0,75	19,5	346,0	670,0	18	26269	34 G 1,5	22,7	671,0	1060,0	16
26242	42 G 0,75	20,9	410,0	960,0	18	26270	42 G 1,5	24,4	890,0	1300,0	16
26243	50 G 0,75	23,2	470,0	1104,0	18	26271	50 G 1,5	26,8	997,0	1677,0	16
26244	61 G 0,75	25,0	550,0	1270,0	18	26272	61 G 1,5	29,6	1120,0	1971,0	16

Dimensions and specifications may be changed without prior notice. (RA05)

Continuation ▶

KOMPOFLEX® JZ-500-C halogen-free, microbes resistant, Cu-screende, EMC-preferred type, meter marking



Part No.	No. cores x cross-sec. mm ²	Outer ø app. mm	Cop. weight kg / km	Weight app. kg / km	AWG-No.
26273	2 x 2,5	10,0	110,0	180,0	14
26274	3 G 2,5	10,7	148,0	215,0	14
26275	4 G 2,5	11,4	169,0	268,0	14
26276	5 G 2,5	12,5	220,0	349,0	14
26277	7 G 2,5	15,0	284,0	404,0	14
26278	12 G 2,5	18,0	470,0	710,0	14
26279	18 G 2,5	21,2	572,0	891,0	14
26280	25 G 2,5	25,5	740,0	1104,0	14
26281	2 x 4	11,6	124,0	300,0	12
26282	3 G 4	12,3	178,0	340,0	12
26283	4 G 4	13,4	234,0	408,0	12
26284	5 G 4	14,8	284,0	504,0	12
26285	7 G 4	16,2	321,0	640,0	12
26286	12 G 4	21,8	581,0	894,0	12
26287	2 x 6	13,5	176,0	391,0	10
26288	3 G 6	14,2	245,0	453,0	10
26289	4 G 6	15,6	316,0	560,0	10
26290	5 G 6	17,0	442,0	680,0	10
26291	7 G 6	18,7	530,0	891,0	10

Part No.	No. cores x cross-sec. mm ²	Outer ø app. mm	Cop. weight kg / km	Weight app. kg / km	AWG-No.
26292	3 G 10	17,8	367,0	730,0	8
26293	4 G 10	19,7	549,0	1004,0	8
26294	5 G 10	21,6	604,0	1170,0	8
26295	7 G 10	24,0	820,0	1405,0	8
26296	3 G 16	20,7	653,0	894,0	6
26297	4 G 16	22,6	807,0	1311,0	6
26298	5 G 16	25,2	940,0	1550,0	6
26299	7 G 16	27,6	1345,0	1820,0	6
26300	3 G 25	26,0	920,0	1430,0	4
26301	4 G 25	28,9	1169,0	1894,0	4
26302	5 G 25	31,8	1420,0	2272,0	4
26303	4 G 35	33,4	1680,0	2310,0	2
26304	5 G 35	37,2	2020,0	2740,0	2
26305	4 G 50	38,2	2370,0	3270,0	1
26306	5 G 50	43,0	2880,0	4080,0	1

Dimensions and specifications may be changed without prior notice. (RA05)

Our Service on the Internet

The screenshot shows the HELUKABEL website interface. At the top, there are navigation links for 'Download centre', 'Logistic centre', 'Company', 'Products', 'Quality', 'News', 'Contact', 'Service', 'Opinion', and 'Imprint'. A search bar is located on the right. Below the navigation, there is a breadcrumb trail 'You are here: Home > Opinion'. The main content area features a 'Photovoltaic system' section with an image of solar panels and a 'Your opinion is important for us' survey titled 'Customer Satisfaction'. The survey includes three questions with a 5-point rating scale (from ++ to --). A 'Send Survey' button is visible. To the right, there is a 'HELUKABEL world-wide' section with a world map and a dropdown menu labeled 'please select...'. The HELUKABEL logo is prominently displayed at the top right of the page.

Your opinion is important to us

The greatest possible satisfaction of our customers is our highest goal. And so your opinion, suggestions or criticism are very important to us. We would be pleased if you could fill out the catalogue of questions and send it to us.

www.helukabel.de