


# DATAPUR-C EMC-preferred type, Cu-screened, PUR-outer jacket, meter marking

B



## Technical data

- Special PVC/PUR control cable, adapted to DIN VDE 0281
- **Temperature range**  
flexing -5 °C to +80 °C  
fixed installation -40 °C to +80 °C
- **Operating top level voltage**  
(not for purposes of high current and power installation)  
0,14 mm<sup>2</sup> 350 V  
as of 0,25 mm<sup>2</sup> 500 V
- **Test voltage**  
0,14 mm<sup>2</sup> 800 V  
as of 0,25 mm<sup>2</sup> 1200 V
- **Insulation resistance**  
min. 20 MOhm x km
- **Mutual capacitance** core/core:  
up to 0,34 mm<sup>2</sup> approx. 120 nF/km  
as of 0,5 mm<sup>2</sup> approx. 160 nF/km
- **Minimum bending radius**  
flexing 10x cable ø  
fixed installation 5x cable ø
- **Radiation resistance**  
up to 100x10<sup>6</sup> cJ/kg (up to 100 Mrad)
- **Coupling resistance**  
max. 250 Ohm/km

## Cable structure

- Bare copper, fine wire conductors, bunch stranded to DIN VDE 0295 cl. 5, BS 6360 cl. 5 and IEC 60228 cl. 5
- structure of conductors bei 0,35 mm<sup>2</sup> = 7 x 0,25 mm<sup>2</sup>
- Special PVC core insulation TI2, to DIN VDE 0281 part 1
- Cores colour coded to DIN 47100
- Cores stranded in layers with optimal lay-length
- Foil taped
- Tinned copper braided screen, approx. 85% coverage
- PUR outer sheath TPU to DIN VDE 0282 part 1, appendix A
- Sheath colour grey (RAL 7032)
- with meter marking, change-over in 2011

## Properties

- Chemical resistance: good against acids, lyes, hydraulic liquids
- High flexibility at low temperature
- High abrasion resistance
- **Resistant to**  
Oils and fats  
Non-alcoholic fuels and kerosene  
Atmospheric influences  
UV-radiation  
Oxygen and ozone  
Microbes and rotting  
Sea and waste water  
Vibrations
- The materials used in manufacture are cadmium-free and contain no silicone and free from substances harmful to the wetting properties of lacquers

## Note

- AWG sizes are approximate equivalent values. The actual cross-section is in mm<sup>2</sup>.

## Application

The specific construction of DATAPUR-C makes this cable type ideal for use in all types of computer systems, office machinery, signal and control units.

DATAPUR-C has uses that go beyond this for example in the field of acoustics, e.g. in telephone systems, intercoms as well as in all areas involving accurate control of weights and measurements. This cable type is noted for its excellent mechanical performance in humid to wet conditions. External high frequency interference is screened out by the tinned copper braiding. These cables are extremely tear and abrasive resistant.

**EMC** = Electromagnetic compatibility

To optimise the EMC features we recommend a large round contact of the copper braiding on both ends.

CE = The product is conformed with the EC Low-Voltage Directive 2006/95/EG.

Part no.	No. cores x cross-sec. mm <sup>2</sup>	Outer Ø approx. mm	Cop. weight kg / km	Weight approx. kg / km	AWG-No.	Part no.	No. cores x cross-sec. mm <sup>2</sup>	Outer Ø approx. mm	Cop. weight kg / km	Weight approx. kg / km	AWG-No.
52490	2 x 0,14	4,0	12,3	21,0	26	52512	2 x 0,34	5,0	17,0	33,0	22
52491	3 x 0,14	4,1	14,0	25,0	26	52513	3 x 0,34	5,2	20,7	42,0	22
52492	4 x 0,14	4,4	15,7	29,0	26	52514	4 x 0,34	5,6	24,7	48,0	22
52493	5 x 0,14	4,8	19,5	35,0	26	52515	5 x 0,34	6,2	30,1	57,0	22
52494	7 x 0,14	5,1	23,4	41,0	26	52516	7 x 0,34	6,7	38,2	77,0	22
52495	10 x 0,14	6,2	28,5	54,0	26	52517	10 x 0,34	8,4	63,1	111,0	22
52496	12 x 0,14	6,5	34,3	64,0	26	52518	12 x 0,34	8,9	74,2	128,0	22
52497	14 x 0,14	6,8	39,9	74,0	26	52519	14 x 0,34	9,3	85,3	144,0	22
52498	18 x 0,14	7,7	51,5	93,0	26	52520	18 x 0,34	10,2	107,4	175,0	22
52499	21 x 0,14	8,0	60,1	108,0	26	52521	21 x 0,34	10,9	124,1	200,0	22
52500	25 x 0,14	8,8	71,9	128,0	26	52522	25 x 0,34	11,9	147,0	233,0	22
52501	2 x 0,25	4,5	14,7	26,0	24	52523	2 x 0,5	5,4	23,2	38,0	20
52502	3 x 0,25	4,7	17,1	33,0	24	52524	3 x 0,5	5,6	30,1	51,0	20
52503	4 x 0,25	5,0	20,6	38,0	24	52525	4 x 0,5	6,2	35,4	58,0	20
52504	5 x 0,25	5,4	24,8	44,0	24	52526	5 x 0,5	6,7	52,6	77,0	20
52505	7 x 0,25	5,8	31,1	53,0	24	52527	7 x 0,5	7,2	65,3	93,0	20
52506	10 x 0,25	7,2	42,0	79,0	24	52528	10 x 0,5	9,3	88,8	134,0	20
52507	12 x 0,25	7,7	51,0	92,0	24	52529	12 x 0,5	9,7	101,9	155,0	20
52508	14 x 0,25	8,1	60,1	105,0	24	52530	14 x 0,5	10,2	115,1	175,0	20
52509	18 x 0,25	9,0	77,9	128,0	24	52531	18 x 0,5	11,4	141,2	214,0	20
52510	21 x 0,25	9,6	91,4	148,0	24	52532	21 x 0,5	11,9	161,1	245,0	20
52511	25 x 0,25	10,7	110,8	175,0	24	52533	25 x 0,5	13,1	187,9	285,0	20

Dimensions and specifications may be changed without prior notice. (RB01)