



HELUKABEL SUPERTRONIC-PVC 4x0,25 QMM / 49563 350 V 001041714

CE



## Technical data

- Special PVC cable for drag chains, adapted to DIN VDE 0245, 0281
- Very high flexible due to special construction
- **Temperature range**  
flexing -5 °C to +70 °C  
fixed installation -40 °C to +70 °C  
(short time +105 °C)
- **Nominal voltage** 350 V
- **Test voltage** 1500 V
- **Breakdown voltage** min. 3000 V
- **Insulation resistance**  
min. 20 MΩm x km
- **Minimum bending radius**  
flexing 5x cable ø  
fixed installation 3x cable ø
- **Radiation resistance**  
up to 80x10<sup>6</sup> cJ/kg (up to 80 Mrad)

## Cable structure

- Bare copper, extra fine wire conductors, to DIN VDE 0295 cl. 6 col. 4 and 5
- Special PVC core insulation T12, to DIN VDE 0281 part 1
- Cores colour coded to DIN 47100, see Technical Informations
- Cores stranded in layers with optimal selected lay-length
- Core wrapping with textile tape
- Special PVC outer sheath TM2, to DIN VDE 0281 part 1
- Colour grey (RAL 7001)
- with meter marking, change-over in 2011

## Properties

- Extensively oil resistant
- Chemical Resistance - see table Technical Informations
- Adhesion-free
- PVC self-extinguishing and flame retardant according to VDE 0482-332-1-2, DIN EN 60332-1-2/ IEC 60332-1 (equivalent DIN VDE 0472 part 804 test method B)
- The materials used in manufacture are cadmium-free and contain no silicone and free from substances harmful to the wetting properties of lacquers

## Note

- AWG sizes are approximate equivalent values. The actual cross-section is in mm<sup>2</sup>.

## Application

The ideal cable for use in cable trays. This high flexible cable is ideal for all areas requiring a high and fast flexing cable including the machine industries, robotics and all areas of highly mobile machine parts. The long working life offers a secure performance as well as economy. For applications which go beyond standard solutions (for example for composting appliances or high shelf conveyors with extremely high processing speeds etc.) we recommend for our especially developed enquiry sheet for energy guiding systems.

Before installation in cable trays please read the instructions. Further technical details see selection table for drag chain cables, see lead text.

CE= The product is conformed with the EC Low-Voltage Directive 2006/95/EG.

Part no.	No. cores x cross-sec. mm <sup>2</sup>	Outer Ø approx. mm	Cop. weight kg / km	Weight approx. kg / km	AWG-No.
49550	2 x 0,14	3,5	2,8	23,0	26
49551	3 x 0,14	3,7	4,1	25,0	26
49552	4 x 0,14	3,9	5,6	30,0	26
49553	5 x 0,14	4,2	7,0	35,0	26
49554	7 x 0,14	4,8	9,8	49,0	26
49555	10 x 0,14	6,2	14,0	64,0	26
49556	12 x 0,14	6,3	16,8	71,0	26
49557	14 x 0,14	6,6	19,6	77,0	26
49558	18 x 0,14	7,2	25,2	90,0	26
49559	24 x 0,14	8,5	33,6	119,0	26
49560	25 x 0,14	8,6	35,0	124,0	26
49561	2 x 0,25	4,2	5,0	28,0	24
49562	3 x 0,25	4,4	7,5	33,0	24
49563	4 x 0,25	4,7	10,0	39,0	24
49564	5 x 0,25	5,6	12,5	50,0	24
49565	7 x 0,25	6,1	17,5	63,0	24
49566	10 x 0,25	7,2	25,0	85,0	24

Part no.	No. cores x cross-sec. mm <sup>2</sup>	Outer Ø approx. mm	Cop. weight kg / km	Weight approx. kg / km	AWG-No.
49567	12 x 0,25	7,5	30,1	95,0	24
49568	14 x 0,25	7,9	35,0	107,0	24
49569	18 x 0,25	8,9	45,0	130,0	24
49570	24 x 0,25	10,4	60,0	170,0	24
49571	25 x 0,25	10,5	62,5	177,0	24
49572	2 x 0,34	4,6	6,8	33,0	22
49573	3 x 0,34	4,8	10,2	42,0	22
49574	4 x 0,34	5,2	13,6	56,0	22
49575	5 x 0,34	6,1	17,0	64,0	22
49576	7 x 0,34	7,0	23,8	84,0	22
49577	10 x 0,34	8,4	34,0	116,0	22
49578	12 x 0,34	8,5	40,8	133,0	22
49579	14 x 0,34	9,0	47,6	150,0	22
49580	18 x 0,34	10,1	61,2	182,0	22
49581	24 x 0,34	12,0	81,5	240,0	22
49582	25 x 0,34	12,2	85,0	250,0	22

Dimensions and specifications may be changed without prior notice. (RC03)